

I Datenblatt I

I AERCUBE-MID-energy-counter-box I

AERIAL[®]
THE DRYING EXPERTS

CC4 MID

Application & Function

Operation	Power distributor for connection of max. 4 consumers with common measurement of energy consumption by means of a calibrated energy meter (MID)
Application	Specially developed for use in construction and water damage drying
Suitability	For all fields of application for which the determination of energy consumption by means of a calibrated energy meter is required for billing purposes.



Performance

Compliant energy meter (MID-compliant), Currentless reading
Tamper-proof with a standard padlock (4-digit lock)
Extremely robust, shock-resistant and UV-resistant rotationally molded plastic housing. Robust and easy-care surface.
5 year warranty on all PE housing parts
user-friendly by fast closing clamps
Optimal grasping and carrying options.
Can be stable and reliable combined and stacked with all AERIAL AERCUBE-products.

Technical data

Number of sockets	4 x built-in plug socket with cover
Fusing	Integrated fuse (16 A) Integrated r.c.c.b. according to EN61009-1, VDE 0664-20: Rated sensor current 30 mA, with test button release
Voltage	230 V / 50-60 Hz
Power cord	4,5 m. with plug
Prot. Class	IP44
Dimensions	Height / Width / Depth 293 / 234 / 346 mm
Weight	4,5 kgs



* Experience values - Valid: Juni 2017 - Subject to change

Version: 2017-09-20

AERIAL GmbH - Oststrasse 148 - 22844 Norderstedt - Phone +49 40 526 879 0 - Fax +49 40 526 879 20
info@aerial.de - www.aerial.de